

REVISED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/092476 A1

(51) International Patent Classification⁷: **B01D 47/00**,
53/34, B01J 8/00

(74) Agent: **MARICH, Eric**; The Babcock & Wilcox Com-
pany, 20 South Van Buren Avenue, Barberton, OH 44203-
0351 (US).

(21) International Application Number:
PCT/US2005/009441

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 21 March 2005 (21.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/555,281 22 March 2004 (22.03.2004) US

(71) Applicant (*for all designated States except US*): **THE
BABCOCK & WILCOX COMPANY** [US/US]; 20 S.
Van Buren Avenue, Barberton, OH 44203-0351 (US).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **DOWNS, William**
[US/US]; 8645 Schubert Avenue, Alliance, OH 44601
(US). **FARTHING, George, A., Jr.** [US/US]; 12276
Cenfield NE, Alliance, OH 44601 (US).

[Continued on next page]

(54) Title: DYNAMIC HALOGENATION OF SORBENTS FOR THE REMOVAL OF MERCURY FROM FLUE GASES



(57) Abstract: A halogen-containing gas is injected into a flowing transport air/sorbent stream at a point close to the point where the sorbent and transport air first mix to maximize the residence time available for the halogen-containing compound to be adsorbed onto the sorbent surface prior to the sorbent being injected into a flue gas containing mercury. This process maximizes the benefit and utilization of the halogen-containing reagent by placing it exactly where it is needed to facilitate elemental mercury removal - on the surface of the sorbent. The sorbent particles with their loading of adsorbed halogen-containing reagent enter the flue gas with a high reactivity for the removal of elemental mercury.

WO 2005/092476 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the revised international search report: 1 December 2005

(15) Information about Correction:
see PCT Gazette No. 48/2005 of 1 December 2005, Section II